BackRiver Townhomes Features

Kitchen Appliances, Cabinets & Counters

Kitchen designed by Metropolitan (options available). Countertops are granite. Jenn Air stainless steel dishwasher, gas range, refrigerator, microwave and disposal.

Fireplaces

All fireplaces are 36" wide prefabricated self contained gas firebox.

Flooring

Hardwood is standard in all first floor common areas including the Powder Room.

The Guest and Master Baths have tile floors.

The stairs and 2nd floor halls are hardwood and the bedrooms are carpeted.

Bathrooms

Tile tub and shower enclosures, Kohler fixtures

Painting

All interior wood trim is prime coated followed by 2 coats semi gloss latex paint. Walls are painted with one prime coat and 2 coats latex flat paint. See standard colors.

Interior trim

Window and door trim 3", baseboard 7 ¼" finger –jointed baseboard molding.

Closet shelving is painted with metal rods.

HVAC

Gas fired forced hot air system with energy-efficient central air conditioning.

Gas fired 50 gallon hot water tank.

Electrical

All homes have 200 amp service.

Recessed lights in kitchen, junction box provided in Dining Room, Foyer and Kitchen.

Exterior lighting at entry, garage and deck/patio.

Integrated Home Wiring

All homes will be pre-wired for television (RG-6) and telephone (Cat-5).

Interior Walls and Insulation

Common Walls- consist of 2 independent 2" x 4" wood framed stud walls with a one inch air space, divided by a 2" gypsum shaft liner of fire code sheetrock on each side and insulated on both sides with 3 ½" of fiberglass sound blanket.

Walls-1/2" blueboard with skim coat plaster.

Smooth ceilings throughout and closet shelving is painted with metal rods.

Windows and Doors

Insulated windows are Anderson with tilt-in sash and grills between the glass.

Front entry door is wood with weather stripping.

Interior doors are solid core 4 panel Masonite doors.

Door hardware is brushed chrome.

Garage doors are wood insulated doors with openers and exterior door hardware has weathered finish with locksets.

Concrete Foundation

Frost free insulated slab on grade or foundation walls depending on location, walls are approximately 10" thick.

There are perimeter drains and damp proofing below grade.

Exterior Construction

Exterior walls are 2 x 4 and/or 2 x 6, 16" on center, siding is white cedar shingle and roofs are architectural asphalt shingles.